DC DISKONTCOMPUTER.com

V6-M4A3000E

Specifications

CPU	**AMD CPU** AMD Phenom™ II Processor Athlon™ II Processor Sempron™ Family Processors Socket AM3
Chipset	**North Bridge:** AMD RS780L **South Bridge:** SB 710
Memory	2 x DIMM DDR3-1066/1333 Support max. 8GB
Expansion Slots	2 x PCI 1 x PCI-e x 1 1 x PCI-e x 16
Graphics	Integrated ATI Radeon™ 3000 Max. resolution: 2048 x 1536 Support Microsoft DirectX 10
OnBoard VGA / max share MEM1024M	
IDE	1 x ATA 133
S-ATA	6 x SATA
LAN	1 x 10/100/1000 Mbps
LAN Chip	Atheroes 8131L-AL1E
Audio	Realtek 1708S Azalia 6 Channel
Dimension (mm) W x H x D	168mm (W) x 354mm (H) x 380mm (D)
Front Panel	2 x USB2.0 1 x Microphone 1 x Headphone
Rear Panel	4 x USB 2.0 1 x PS/2 Keyboard 1 x PS/2 Mouse 1 x RJ45 LAN 1 x D-sub 1 x DVI
Power Supply	Peak 380W (PFC)
O/S Support	Windows 7 Windows Vista Windows XP
Manageability	PXE WOL WOR by PME WOR by Ring
Noise Level	Idle mode: 28dB
Key Features	ASUS AI manager ASUS CrashFree BIOS2 ASUS DriveClone Pro 7 ASUS Express Gate ASUS My Logo2 ASUS EPU PC Cillin AntiVirus Solution

- All specifications are subject to change without notice. Please check with your supplier for exact offers. Products may not be available in all markets.
- PCB color and bundled software versions are subject to change without notice.
- Brand and product names mentioned are trademarks of their respective companies.